

Project:

Item:

Quantity:

MEGA F-940

VACUUM PACKING MACHINE



DESCRIPTION

The robust, stainless steel Mega F-940 vacuum packaging machine is standard equipped with a Busch vacuum pump, a transparent lid and 2 seal bars. This machine is ETL listed and complies with UL, CSA and CE standards.











FEATURES

- Standard with 2 seal bars (left-right):
 2 x 12.6"
- Standard Double seal (2 wires).
 Optional without extra costs: Cutoff/Wide seal
- Seal bars easily removable for cleaning and maintenance purposes
- Pump capacity: 2,780 cf/h (75 m³/h) Busch vacuum pump
- Pump maintenance and cleaning program
- Machine cycle: 15-40 sec
- Sensor control: max. 99.8%, for an optimum vacuum and cycle time
- Standard with Fragile/Soft Air function to protect the product and vacuum pouch
- 10 program memory
- Transparent lid, which opens automatically after every cycle
- Comes with insert plates for a faster cycle and product adjustment

OPTIONS AND ACCESSORIES

- 2 seal bars (left: 11", front: 37")
- Advanced Control System (ACS)
- Liquid Control (for packing liquids)
- Gas flush
- Inclined insert plate
- Food container adaptor
- label printer (only in combination with ACS)
- Service kit for standard maintenance

WARRANTY

Pack 3000 offers a warranty of 1 year on labor and 3 years on parts. For full warranty details, please refer to www.pack3000.com

DATE APPROVAL




PACK 3000 Sales and technical support


sales@pack3000.com


VACUUM PACKAGING MACHINE MARLIN 90 <u>- SPECS</u>

DIMENSIONS

In inches







Model	el Dimensions (inches)		Volts	Amps	Hz	Pump	HP	Plug	Weight
	Chamber (usable space) LxWxH	Machine LxWxH				capacity			(lbs)
Mega F-940	12.6"x35"x3.9"	18.8"x42"x38.2"	208- 220V	17/ 17 C*	60Hz	2,780 cf/h (75 m3/h)	3.2	NEMA L15-30P	482



3 pole, 4 wire grounding 3 x 208 Volt

*This is the minimum fuse value with the recommended characteristic



PACK 3000 Sales and technical support

sales@pack3000.com